

Clutch tips

- Use Hinson clutch plates in your clutch for the best performance.
- Soak your clutch plates in oil before installing them
- We recommend using petroleum based 80 weight Transmission oil
- Change the oil after each time you ride.
- Always maintain 1/8" to 1/4" of free play at the lever and perch.

For other parts available for this model visit Hinsonracing.com

Warranty information

All merchandise manufactured by Hinson Clutch Components is guaranteed against defects in material and workmanship for a period of six months from the original date of purchase. Use of Kevlar and carbon fiber clutch plates will cause excessive wear and will void your warranty. Hinson Clutch Components will not warranty any product that has been modified, or where the product became defective due to improper installation, improper use, or any other misuse of the product. Hinson Clutch Components shall not be liable for any other damages caused by any defects in the product, whether incidental, consequential or otherwise. You must return the warranty card to validate your warranty. If your product is defective we will, at our discretion, repair or replace the product after it is returned to Hinson Clutch Components for a warranty inspection. Any request for warranty assistance will require your original receipt or acceptable proof of purchase. Hinson Clutch Components liability is limited to the cost of repair or replacement of the product. All warranty items will be viewed and acted upon at the discretion of Hinson Clutch Components.

THANK-YOU FOR BUYING A HINSON CLUTCH COMPONENT!



Billetproof Clutch Basket w/ Cushions, Kickstarter and Primary Gears Yamaha YZ85

Thank you for purchasing Hinson Clutch Components. Please enjoy the high level of factory performance we have included in this package. Looking through these instructions will ensure your machine is on the way to its highest level of performance.

H160



1630 W. 11th St. Unit E, Upland, CA 91786


p 909.946.2942 | f 909.985.2301 | www.hinsonracing.com

1. Remove stock basket

- Remove the pressure plate and the inner hub.
- Remove the basket from the bike.

2 Re-install clutch

- Re-install new assembled Hinson clutch basket, your inner hub, plates, pressure plate, springs, and bolts.



* It is crucial that you use RED Loctite #272. To insure proper bonding of the surfaces you need to clean the threads thoroughly with a contact cleaner, acetone, or another cleaning/degreasing solution. To make the bond even stronger you should use a Loctite primer. It is important that you use fresh Loctite since it has a shelf life. To ensure a permanent hold you need to put Loctite into the hole and also onto the screw. Keep in mind that you cannot use too much, you want complete coverage with the Loctite.