



Also available for this model:

- Clutch Cover



FSC Clutch Plate & Spring Kit

Triumph TF450-RC (See website for fitment)

Thank you for purchasing Hinson Clutch Components. Please enjoy the high level of factory performance we have included in this package. Looking through these instructions will ensure your machine is on the way to its highest level of performance.

FSC106-8-2501

Thank you for purchasing a Hinson Clutch Components product. If you have any questions or need technical assistance, please call us at (909) 946-2942, Monday through Friday between the hours of 7:30AM-4:30PM Pacific Standard Time or check us out at www.hinsonracing.com.



1630 W. 11th St. Unit E, Upland, CA 91786

p 909.946.2942 | f 909.985.2301 | www.hinsonracing.com | @hinsonracing



1630 W 11th ST, UNIT E, UPLAND, CA 91786 909.946.2942, 909.985.2301 FAX
www.hinsonracing.com

FSC Clutch Plate & Spring Kit Triumph TF450-RC

Congratulations, you have just purchased the finest fiber, steel and spring clutch pack available. Hinson Clutch Components are used by Team Honda, Team KTM, Team Triumph and Team Pro Circuit Kawasaki.

Instructions:

1. Drain engine oil
2. Remove clutch cover paying attention to the O-ring gasket in the big outer cover
3. Remove the bolts, spring retainer, spring, spring seat and pressure plate
4. Remove the used clutch stack and OEM pins
5. Reinstall the new Hinson fibers, steels and pins starting with a thin steel plate first. Next a fiber plate, then one of the (7) thicker steel plates alternating fiber steel then ending with a thin steel plate.
6. Reinstall pressure plate and spring seat, the Hinson spring, spring retainer and bolts. Torque them to OEM specifications (Note: You may need to push down on the pressure plate slightly to compress the slave cylinder to allow the pressure plate to properly engage the outer steel plate before you bolt up spring).
7. Reinstall clutch cover being sure to inspect the O-ring gasket before reinstalling. Refill with engine oil to manufacture's specification.

We recommend petroleum 10w-40 Racing Engine Oil, and that you change it after each time you ride. Also we recommend soaking your clutch plates in oil before you install them.

***Note you must use the Hinson Friction plates and steel plates together. Failure to use both together will result in damage and possible failure of the clutch**



Warranty information

All merchandise manufactured by Hinson Clutch Components is guaranteed against defects in material and workmanship for a period of six months from the original date of purchase. Use of Kevlar and carbon fiber clutch plates will cause excessive wear and will void your warranty. Hinson Clutch Components will not warranty any product that has been modified, or where the product became defective due to improper installation, improper use, or any other misuse of the product. Hinson Clutch Components shall not be liable for any other damages caused by any defects in the product, whether incidental, consequential or otherwise. If your product is defective we will, at our discretion, repair or replace the product after it is returned to Hinson Clutch Components for a warranty inspection. Any request for warranty assistance will require your original receipt or acceptable proof of purchase. Hinson Clutch Components liability is limited to the cost of repair or replacement of the product. All warranty items will be viewed and acted upon at the discretion of Hinson Clutch Components.

Thank you very much for purchasing a Hinson Clutch Component!